

08038DA(E-Type Three Phase)

Server(Telecom)

2023/12/27

General Specifications




Motor Protection: Auto Restart / Polarity Protection
 Insulation Resistance: 10M ohm or over with a DC500V Megger
 Dielectric Withstand Voltage: AC700V 1s
 Allowable Ambient Temperature Range : -10deg.C - +70deg.C (Operating)
 -40deg.C - +70deg.C (Storage)
 non-condensing environment


Expected Life

40deg.C 70,000 Hours *Failure Rate 10% (L10 Life)

Outline



Panel Out-cuts




08038DA(E-Type Three Phase)

Server(Telecom)

2023/12/27

Characteristic Curves



Material

Casing: Plastic (Black) UL94V-0

Impeller: Plastic (Black) UL94V-0

Bearing: Ball

Bearing Lead Wire: UL3385 AWG20 +: Red, -: Black

* Variable speed type is also available.

Please inquire regarding the other requirements.

Specifications

Model	Product No	Nominal Voltage [V]	Operating Voltage lower limit [V]	Operating Voltage upper limit [V]	Current [A]	Input Power [W]

08038DA(E-Type Three Phase)

Server(Telecom)

2023/12/27

08038DA-12T-E6E-0	0	12	10.8	13.2	6.00	72.00	
Model	Speed [min-1]	Max. Air Flow [m3/min]	Max. Air Flow [CFM]	Max. Static Pressure [Pa]	Max. Static Pressure [In H2O]	Noise [dB]	Mass [g]
08038DA-12T-E6E-0	18000	3.90	137.70	1430.0	5.73	80.0	240.0

Rotation: Clockwise as seen from the label side

Airflow Outlet: Label side

*1: Average Values in Free Air