




# MMJ65A0F00\*\*



### Outline

IGBT (Bare chip) utilizes various technologies that we cultivated by analog semiconductor device production and is the product which prepared a lineup of the wide high voltage, high current which can contribute to high efficiency and saving energy.

### Applications

- Industrial Motor Drivers
- Inverter
- Welding
- UPS

### Features

- ① Field Stop Trench gate IGBT
- ② Low Collector-Emitter saturation voltage
- ③ High short circuit capability
- ④ Low switching losses

### Absolute Maximum Ratings

Tj=25deg unless otherwise noted.

Parameter	Symbol	Rating	Unit
Collector-Emitter voltage	VCES	650	V
Gate-Emitter voltage	VGES	±30	V
Collector current *1)	IC	100	A
Junction temperature	Tj	-40~+175	°C

\*1)Collector current is limited by Tj(max) and thermal properties of assembly.

### Die Specification

Item	Value	Unit
Die thickness	90	μm
Die size	6.0x9.0(54.0)	mm
Front metal(AlSi)	6.5	μm
Backside metal(AlSi/Ti/Ni/Au)	1.25	μm

### Electrical Characteristics

Tj=25deg unless otherwise noted.

Parameter	Symbol	Specification			Unit	condition	
		Min	Typ	Max			
Zero gate voltage collector current	ICES	-	-	1	μA	Vce=650V,Vge=0V	
Gate-Emitter leakage current	IGES	-	-	±500	nA	Vge=±30V,Vce=0V	
Gate-emitter threshold voltage	VGE(th)	5.20	-	6.60	V	Vce=10V,Ic=1.6mA	
Collector-Emitter saturation voltage	VCE (sat)	Tj=25°C	-	1.45	1.75	V	Ic=100A,Vge=15V
		Tj=150°C	-	1.70	-		
		Tj=175°C	-	1.75	-		
Internal gate resistor	Rgint	-	1.70	-	Ω		
Input capacitance	Cies	-	7200	-	pF	VCE=25V,VGE=0V, f=100kHz	
Reverse transfer capacitance	Cres	-	120	-	pF		
Switching time *Reference characteristics	td(on)	-	65	-	ns	Vcc=300V,Ic=100A VGE=-15/+15V, Rg=8.2Ω, Inductive load, Ls≒100nH	
	tr	-	45	-	ns		
	td(off)	-	200	-	ns		
	tf	-	200	-	ns		
Short circuit withstand time	Tsc	10	-	-	μs	Vcc=400V,Vge=15V,Tj=150°C	

This characteristic is when it is incorporated in a mold package or evaluation board.

Depending on the assembly conditions etc., it may not be satisfied. Please note that it is not a guaranteed value.

### Die Dimension

