

# MM1856

2023/07/20

## Overview

This IC is a 200mA Low dropout regulator IC with ON/OFF control.

The IC applies to a standard home equipments, for a maximum operating voltage is 14V.

Package is a small SOT-25A, SC-82ABB.

## Application

- Audio visual equipment
- Office equipment / Printer
- Home appliance equipment

## Features

15V Maximum ratings input voltage

## Main specifications

Output current [mA]	200
Absolute maximum rating [V]	15.0
Recommended operating voltage Min. [V]	1.80
Recommended operating voltage Max. [V]	14.0

**MM1856**

2023/07/20

Output voltage Min. [V]	1.50
Output voltage Max. [V]	5.00
Output voltage accuracy [%]	±2.0
No-Load Input Current [μA]	75.0
Dropout Voltage [V]	0.30
PSRR [dB]	70
Output capacitor [μF]	1.00
Circuit structure	1ch LDO
Operating ambient temperature Min. [deg.C]	-40
Operating ambient temperature Max. [deg.C]	85
OFF input current Typ. [μA]	0.00
Protection function	OCP, TSD
Additional function	ON/OFF control

**Package**[SC-82ABB](#)[SOT-25A](#)

# Case Studies

No amplifier or software design required. Development of an LDO for automobiles with open load/short circuit detection function. [Power Supply IC]