

MM1886

2023/07/20

Overview

This IC is a 250mA/300mA Low dropout regulator IC with ON/OFF control.

The IC applies to a standard home equipments, for a maximum operating voltage is 14V.

Application

- Audio visual equipment
- Office equipment / Printer
- Home appliance equipment

Features

15V Maximum ratings voltage

Main specifications

Output current [mA]	300
Absolute maximum rating [V]	16.0
Recommended operating voltage Min. [V]	1.80
Recommended operating voltage Max. [V]	14.0
Output voltage	

MM1886

2023/07/20

Min. [V]	1.50
Output voltage Max. [V]	5.00
Output voltage accuracy [%]	±2.0
No-Load Input Current [μA]	75.0
Dropout Voltage [V]	0.45
PSRR [dB]	70
Output capacitor [μF]	1.00
Circuit structure	1ch LDO
Operating ambient temperature Min. [deg.C]	-40
Operating ambient temperature Max. [deg.C]	85
OFF input current Typ. [μA]	0.00
Protection function	OCP, TSD
Additional function	ON/OFF control

Package

[SOT89-5A](#)

[SOT-25A](#)

[SSON-6A](#)

Case Studies



No amplifier or software design required. Development of an LDO for automobiles with open load/short circuit detection function. [Power Supply IC]