

MM3404

2023/07/20

Overview

This IC is a high speed response 200mA regulator IC with low quiescent current and high ripple rejection. No load input current is 20 μ A typ.

and ripple rejection is 75dB typ. Dropout voltage is low at 80mV typ., and the output current is 200mA.

Therefore the IC applies to most mobile equipment.

Application

- Audio visual equipment
- Photographing / Imaging device
- Office equipment / Printer
- Home appliance equipment

Features

High ripple rejection

Main specifications

Output current [mA]	200
Absolute maximum rating [V]	7.0
Recommended operating voltage Min. [V]	1.60
Recommended operating voltage	

MM3404

2023/07/20

Operating voltage Max. [V]	6.5
Output voltage Min. [V]	0.80
Output voltage Max. [V]	5.00
Output voltage accuracy [%]	±1.0
No-Load Input Current [μA]	20.0
Dropout Voltage [V]	0.08
PSRR [dB]	75
Output capacitor [μF]	1.00
Circuit structure	1ch LDO
Operating ambient temperature Min. [deg.C]	-40
Operating ambient temperature Max. [deg.C]	85
OFF input current Typ. [μA]	0.01
Protection function	OCP
Additional function	ON/OFF control, Auto discharge

Package

SC-82ABB

SOT-25A

Case Studies



No amplifier or software design required. Development of an LDO for automobiles with open load/short circuit detection function. [Power Supply IC]