

Check rod method mounting attachment CCA-CC002-*

2023/03/22

Features



- Equipped lift-off protection fitting as a standard
- There is allowable moving length in horizontal direction for the thermal expansion such as tanks.

Specification

Specification name	Specification contents
Applicable load cell	CC002-10T~30T、DC002-10T~40T
Allowable horizontal moving length	±7 mm(No directionarity)
Material	SS400 or equivalent (Electroless nickel plating)
Accessories	Bolt for stop floating, Washer, Eyebolt, Tacking bolt, Instruction manual

Item list

Applicable	Allowable horizontal	Allowable lifting	Weight(Approx.)	Material	3D CAD files	CAD files(DXF)

Check rod method mounting attachment CCA-CC002-*

2023/03/22

load cell	load [%R.C.]	load [%R.C.]	[kg]	Material	[STEP]	CAD files[DXF]
CC002-10T/-20T, DC002-10T/-20T	±60	±50	30	SS400 or equivalent (Electroless nickel plating)	CCA-CC002-10T~20T.STEP	fca_cc010_20t.dxf
CC002-25T/-30T, DC002-25T/-30T	±60	±50	42	SS400 or equivalent (Electroless nickel plating)	CCA-CC002-25T~30T.STEP	fca_cc010_30t_50t.dxf