

Flexible stop method mounting attachment FCACC010-*B (S) series

2023/03/22

Features



- Equipped with lift-off protection fitting
- All stainless steel construction (Available for alloy steel construction)
- Most suitable for the tank where the vibration such as pugmill is generated.

Specification

Specification name	Specification contents
Applicable load cell	CC010-500K~50T / CC010-2T~50T-C3
Allowable horizontal moving length	±8 mm (with directionarity)
Material	SUS304 or equivalent / SS400 or equivalent (Electroless nickel plating)
Accessories	Guide plate, Hexagon socket head cap screws, Instruction manual, Dummy load cell, Lift-off protection fitting, Washer, Earth cable

Item list

Flexible stop method mounting attachment

FCACC010-*B (S) series

2023/03/22

Item	Applicable load cell	Allowable horizontal load [kN]	Allowable horizontal load [tf]	Allowable lifting load [kN]	Allowable lifting load [tf]	Weight(Approx.) [kg]
FCACC010-3B*	CC010-500K(-C3)~ CC010-50T(-C3)***	±29.42	±3.00	±39.23	±4	17
FCACC010-6B*	CC010-500K(-C3)~ CC010-50T(-C3)***	±58.84	±6.00	±78.46	±8	21
FCACC010-12B*	CC010-500K(-C3)~ CC010-50T(-C3)***	±117.7	±12.00	±117.7	±12	34
FCACC010-3B*S	CC010-500K(-C3)~ CC010-50T(-C3)***	±29.42	±3.00	±39.23	±4	17
FCACC010-6B*S	CC010-500K(-C3)~ CC010-50T(-C3)***	±58.84	±6.00	±78.46	±8	21
FCACC010-12B*S	CC010-500K(-C3)~ CC010-50T(-C3)***	±117.7	±12.00	±117.7	±12	34

Item	Material	3D CAD files [STEP]	CAD files[DXF]
FCACC010-3B*	SS400 or equivalent (Electroless nickel plating)	FCA-CC010-3BS.STEP	fca_cc010_500k_10t.dxf
FCACC010-6B*	SS400 or equivalent (Electroless nickel plating)	FCA-CC010-6BS.STEP	fca_cc010_20t.dxf
FCACC010-12B*	SS400 or equivalent (Electroless nickel plating)	FCA-CC010-12BS.STEP	fca_cc010_30t_50t.dxf
FCACC010-3B*S	SUS304 or equivalent	FCA-CC010-3BS.STEP	fca_cc010_500k_10t.dxf
FCACC010-6B*S	SUS304 or equivalent	FCA-CC010-6BS.STEP	fca_cc010_20t.dxf
FCACC010-12B*S	SUS304 or equivalent	FCA-CC010-12BS.STEP	fca_cc010_30t_50t.dxf

Options

Welding plate FCAW-*